

1.2.3.1. Tender text Swivel jet nozzle, type DW-V2

... units

Swivel jet nozzle with rounded intake featuring good aerodynamic and acoustic properties, housed in a hemispheric casing with opposite swivel bearings, swivel range $\pm 30^\circ$, designed as jet nozzle with large jet penetration depth for air distribution into large spaces, discharge direction adjustable in the horizontal and vertical planes,

fitted with:

fastening flange to accommodate the hemisphere and the nozzle, turnable within slot segments for setting the discharge direction as required; a scale with 10-degree division helps set the discharge direction accurately when tuning the HVAC system. The discharge direction can be adjusted manually, by electric actuator or, without auxiliary energy, by a self-acting thermostatic control unit. With thermostatic control unit, the factory-set swivel range can be altered manually once the swivel jet nozzle is installed; this is possible in increments of 5° and up to 20° in total. The mechanism of the thermostatic control unit is protected from undue application of force by a device that can disengage and engage again when the nozzle is swivelled by hand.

- **Connection type K** with flange for connection to a pressurized plenum or a rectangular duct, inclusive of collar to conceal the fastening screws.
- **Connection type R** with push-in end for insertion into a circular duct to EN 1506, with seal.
- **Connection type F** with slip-on end for shaped parts to EN 1506.
- **Connection type B** with connector for flexible duct.

Material:

- Nozzle body and collar made of aluminium in natural colour or painted to RAL
- Push-in and slip-on ends made of galvanized sheet metal

Make: KRANTZ KOMPONENTEN
Type: DW-V2

Subject to technical alternations.

Krantz GmbH

Uersfeld 24, 52072 Aachen, Germany
Phone: +49 241 441-1, Fax: +49 241 441-555
info@krantz.de, www.krantz.de